

Tradies Choice – Master Primer

Tradies Choice Master Primer

DESCRIPTION

Tradies Choice Master Primer is a fast-drying water based acrylic primer.

Used for porous and non-porous substrates such as existing tiles, Vinyl and carpet and vinyl adhesive residue.

Can be used over old water based paints (not to be used over oil based paints.)

TRADIES CHOICEK

SURFACE PREPERATION

The surface must be clean, dry firm and free of dust oil, grease, wax and curing compounds. The substrate must be install according to the relevant standards and manufacturer recommendations. All porous surfaces must be primed with SAS Master Primer. For non -porous surfaces such as existing tiles, adhesives must be primed using SAS Master Primer neat. Please contact SAS Technical Team for further information.

APPLICATIONS

Porous:

Priming of porous substrates such as concrete f/c sheet dilute Master primer 3 parts water to 1-part Master Primer. Apply primer by roller or brush making sure the entire area is primed.

Allow to cure for 25 minutes before tiling or waterproofing.

Non-Porous

Priming of non-porous substrates such as existing tiles clean the tiles with sugar soap and then clean before applying the Master Primer neat.

Once the Master Primer is cured which is approximately 2 hours @ 23 °C you can apply a levelling compound or Tile adhesive.

COVERAGE

Porous substrate: 9m2 per Litre Non-Porous substrate: 6m2 per Litre





Tradies Choice – Master Primer

PACKAGING

Master Primer is available in 1L,5L containers.

Precautions

- Do not apply Master Primer on substrates subject to rising damp.
- Do not apply Master Primer on tiles that have wax or any other containments.

Technical Data

Appearance – Orange liquid

SDS is available from www.sas-aa.com.au





SAS Australasia Pty Ltd 1300 202 894 WWW.SaS-aa.com.au

ABN: 83 617 827 282

P2

Date:1.10.17